



GNT570-UHF

Handheld Terminal
RFID 868 - 956 Mhz (FHSS) 4w EIRP
EPC Gen 2 & ISO-18000-6B/C
Read Range; 5 meters

GNT570-HF

Handheld Terminal
RFID 13.56MHz (±7KHz)
ISO 15693, 14443A, B / ISO-18000-6C
Read Range; 5 cm

Standard unit configuration and performance details

Operating System:	Microsoft® Windows™ CE 5.0
CPU:	Intel® Bulverde™ PXA 270 520MHz
Memory:	128MB RAM/128MB ROM (Max 256MB)
Display:	3.5" QVGA with backlight, TFT-LCD, 256K colors, 240W x 320 L (QVGA size)
KEY:	24+1 Alphanumeric Key, 2 scanner buttons, Power Button
Audio:	Speaker, Microphone, Headset Jack
I/O:	RS232C, UBS1.1 & WLAN (or Blue Tooth)
Laser	1D Barcode
Operating Temp:	Range; -20°C to 60°C
Humidity:	5~95% Non-Condensing
Drop Specification:	1.5 meter drop to concrete, 6 drops per side, 3 angles
Rating:	IP65 Sealing; Dust & Water Proof / RoHS
Dimensions:	Length; 17.5 cm x Width; 7.4 cm x Height; 2.3cm (3.2cm)
Weight:	Standard Configuration – 380 grams (0.85 lbs)
Battery:	Main Lithium Ion (rechargeable) 3.7V, 3000mAh
Backup Power:	Li-ion Polymer battery (rechargeable) 3.7V 200mAh
Charger:	Adapter/Power Supply & USB Cable
Software:	SDK programming kit
Warranty:	Limited, One Year

Accessories & Options

Bluetooth for Mobil Printer
POS Printer
Additional Battery
2D Barcode Reader
GSM/GPRS EGSN900, GSM1800/1900
Battery Charger (2 Slots)
Gun handle with battery 3.7V, 4400mAh
GPS (Sirf3)
Extended Warranty

SDK programming kit
Bluetooth Printer
Vehicle Cradle
USB Data Cable
Magnetic Stripe Reader
Camera Module
Cradle
Leather Case





